




The Trusted Metal Conveyor Belt Manufacturer



Designed for demanding

Flat-Flex[®] XT[®] Conveyor Belt

medium duty applications

When you require extra strength and support from your belt look no further than Flat-Flex[®] XT[®]. Flat-Flex[®] XT's unique smaller spaces increase the amount of joints across the width of the belt making the belt stronger. Flat-Flex[®] XT's unique design enables superior distribution of product weight across the width of the belt, reducing metal fatigue and increasing belt life.

Advantages

- Over 2X the life of standard belts
- More joints across the belt for longer belt life
- Up to 90% belt strength increase over standard Flat-Flex[®] belts
- Clean-in-place, wash down design
- Up to 78% open area for maximum air/liquid flow through
- Smooth carrying surface lessens product damage
- Available with C-Cure-Edge[®] loops
- USDA Accepted



Wire Belt Company Ltd, Castle Road
Eurolink Industrial Centre, Sittingbourne, Kent ME10 3RF
Tel: +44 (0) 1795 421771 | Fax: +44 (0) 1795 428905 | Email: sales@wirebelt.co.uk


www.wirebelt.co.uk

Flat-Flex[®] XT[®] Conveyor Belt

Available Specifications


XT Code Reference	Pitch and Wire Diameter	Nominal opening between wires	Edge Loop Size	XT Space Width	Minimum Large Space Width	Minimum Transfer Outside Diameter	Typical Open Area (%)
X426	7.26 x 1.6	5.66	7	22.23	50.8	19	71
X247	12.7 x 1.83	10.87	7	22.23	44.45	25	78
X327	9.6 x 1.83	7.77	8	22.23	57.15	25	74
X328	9.6 x 2.08	7.52	8	25.4	82.55	25	72

Edge Loop Types Available




Drive Components

With Flat-Flex[®] XT[®] conveyor belt, setting up your drive and idler shaft is fast and simple.



To setup the drive shaft, install one drive sprocket per XT space along the full width of the drive shaft (figure above). Ensure all sprocket teeth are fully aligned.



In setting up the idler shaft, install one drive sprocket per outside XT space of your belt (figure above). Then, install one blank on each of the inside XT spaces across the width of the belt. Additional sprockets, interspaced across the width, maybe required for wider belts. Contact Wire Belt Technical Sales for more information.